



SATURVAP/232 90N - EN ISO 6134

For the transport of saturated steam

Mandrel built steam hose designed for use with saturated steam up to 210 °C / 18 bar and peaks of superheated steam up to 232 °C. Complying with ISO 6134 type 2A.

Flow medium:

Hot Water, Steam

Marking:

According to norm








Standard / Approval:

EN ISO 6134 - Typ 2A

Description:

- **Inner lining:** Black smooth rubber, heat and steam resistant. Specially developed to avoid cracking and hardening
- **Reinforcements:** High strength spiral wire
- **Cover:** Black, smooth conductive rubber, resistant to abrasion, heat, ozone and weather. Pin pricked to evacuate gases. Fabric impression
- **Working pressure up to:** 18 bar
- **Nom. Burst Pressure:** >180 bar
- **Temperature:** -40 °C +210 °C

Technical data:

INDEX							
nr	mm	mm	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. kg/m
-	13	25	-	-	-	-	0,56
-	19	33	-	-	-	-	0,78
-	25	40	-	-	-	-	1,06
-	32	48	-	-	-	-	1,41
-	38	54	-	-	-	-	1,68
-	51	69	-	-	-	-	2,47
-	63	81	-	-	-	-	3,20
-	76	94	-	-	-	-	3,92

1 - Pressure based on room temperature.

To guarantee the efficiency during the time it is necessary to drain the hose after every use (discharge the condensate).