



COLLECTOR®

Recommended by milk delivery drivers

Applications:

Milk collection vehicles, milk processing industry, milk reception

Flow medium:

Dairy products, milk

Marking:

2 parallel, red stripes interrupted by the words, applied in a spiral on a blue background "Continental COLLECTOR® FDA Glas-/Gabel-Symbol BfR EG 1935/2004 2023/2006 Made in Germany"

Standard / Approval:

FDA Regulation 1772600
BfR Recommendation XXI Cal. 2
EU 1935/2001 2023/2006

Description:

- **Inner lining:** NR, white, absolutely neutral to taste and odour, homogenous, non-porous
- **Reinforcements:** Synthetic fibres with integrated steel wire helix
- **Cover:** NR, blue, fabric patterned, abrasion resistant, resistant to ozone, weather and UV
- **Working pressure up to:** 6 bar / 87 psi
- **Temperature range:** from -40 °C / -40 °F up to +70 °C / +158 °F up to +90 °C / +194 °F (max. 20 minutes)
- **Dampable up to:** +130 °C / +266 °F (max. 20 minutes)
- **Further properties:**
 - Highly flexible
 - Lightweight
 - Recommended fittings system PAGUFIX®

Technical data:

INDEX									
nr	mm	mm	mm	m	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	38	5,5	49	40	6	18	-0,8	76	1200
-	40	5,5	51	40	6	18	-0,8	80	1300
-	45	5,5	56	40	6	18	-0,8	90	1400
-	50	5,5	61	40	6	18	-0,8	100	1500
-	53	5,5	64	40	6	18	-0,8	106	1600
-	63	6	75	40	6	18	-0,8	126	2200
-	65	7	79	40	6	18	-0,8	140	2500
-	75	7	89	40	6	18	-0,8	170	3000
-	100	8	116	40	6	18	-0,8	250	4550

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.