



CONTI ALLCRETE® PRO WIRE - 130BAR

High quality for high pressure concrete lines

Applications:

Concrete and soild pumps

Flow medium:

Concrete

Marking:

3 orange axially applied stripes on black cover "Continental ALLCRETE® PRO WIRE DN 125 (5") - 130 BAR (1885 PSI) - SF2 - 40,0kg/m (26,9lbs/ft) "

Description:

- **Inner lining:** Special elastomer, black, highly abrasion resistant (acc. to DIN ISO 4649-A: <60mm³), smooth
- **Reinforcements:** High tension steel wire
- **Cover:** Spezial elastomer, black, fabric patterned, abrasion resistant, resistant to ozone, weather and UV
- **Working pressure up to:** 130 bar / 1885 psi
- **Temperature range:** from -40 °C / -40 °F up to +90 °C / +194 °F
- **Further properties:**
 - Available flange systems: Victaulic, Heavy Duty (US), etc.
 - Couplings are partly hardend and with galvanized sleeve
 - Fixed lengths with built-in couplings acc. to customers request

Technical data:

INDEX									
nr	mm	mm	mm	m	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	125	15	155	40	130	260	-0,8	1250	11500

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.