

# CONTI® CEMENT SILO

## The reliable specialist

### Applications:

Building material stores, cement plants, cement silo trucks, forwarding agents

### Flow medium:

Cement, concrete, gravel, sand










### Marking:

3 orange, axially applied stripes on black cover " Continental CEMENT SILO DN 75 PN 6 BAR / 87 PSI Made in Germany"

### Description:

- **Inner lining:** SBR, black, highly abrasion resistant, non-porous, smooth
- **Reinforcements:** Synthetic fibres with copper wire
- **Cover:** SBR, black, fabric patterned, abrasion resistant, resistant to ozone, weather and UV
- **Working pressure up to:** 6 bar / 87 psi
- **Temperature range:** from -20 °C / -4 °F up to +70 °C / +158 °F
- **Further properties:**
  - Electrically conductive,  $R < 10^6 \Omega/m$

### Technical data:

INDEX									
nr	mm	mm	mm	m	bar <sup>1</sup>	bar <sup>1</sup>	bar <sup>1</sup>	aprx. mm	aprx. g/m
-	50	9	68	40	6	18	-	500	1980
-	75	9	93	40	6	18	-	750	2770
-	100	10	120	40	6	18	-	1000	4020

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.