



CONTI® FLUX HOSE - RED

For the safe transport of fluxes and fuel gases

Applications:

Welding and brazing machines

Flow medium:

Fuel gases mixed with fluxes and oxygen

Marking:

On red cover "Continental FLUX 6,5 x 12,5 DIN EN ISO 3821 2MPa (20 BAR / 290 PSI) Made in Germany W/J/TC"

Standard / Approval:

DIN EN ISO 3821:2020

Description:

- **Inner lining:** PA, black, impermeable, seamless
- **Reinforcements:** Synthetic fibres
- **Cover:** CSM-BR, red, smooth, abrasion resistant, resistant to ozone, weather and UV
- **Working pressure up to:** 20 bar / 290 psi
- **Temperature range:** up to +90 °C / +194 °F
- **Further properties:**
 - Can also be used for welding processes with aggressive filler agents
 - Highly flexible
 - Robust

Technical data:

INDEX									
nr	mm	mm	mm	m	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	3,2	1,9	7	> 10	20	60	-	50	36
-	6,5	3	12,5	> 10	20	60	-	60	97
-	9	3,5	16	> 10	20	60	-	80	115

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.