



CONTI® PREMIUM SUCTION SD

Suction hose for sewer cleaning suitable for all reel types

Applications:

Sewer cleaning vehicles

Flow medium:

Abrasive bulk material, Water

Marking:

3 orange, axially applied stripes on black cover "Continental PREMIUM SUCTION SD DN 100 PN 6 BAR / 87 PSI Made in Germany" "Continental PREMIUM SUCTION SD DN 100 PN 6 BAR / 87 PSI Made in Germany"

Description:

- **Inner lining:** SBR-BR, black, highly abrasion resistant, homogenous, seamless, smooth
- **Reinforcements:** Synthetic fibres with integrated steel wire helix
- **Cover:** SBR-BR, black, fabric patterned, abrasion resistant, resistant to ozone, weather and UV
- **Working pressure up to:** 6 bar / 87 psi
- **Temperature range:** from -40 °C / -40 °F up to +80 °C / +176 °F
- **Further properties:**
 - Electrically conductive, $R < 10^6 \Omega/m$
 - Long-lasting

Technical data:

INDEX							
nr	mm	mm	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	100	116	6	15	-0.9	400	4300
-	125	145	6	15	-0.9	500	6300
-	150	172	6	15	-0.9	600	8100

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.