



TRIX® PROPANE GAS HOSE

Quality and Safety according to DIN EN 16436-1:2016

Applications:

Mushroom heaters, grills, flame weeding devices, pressure controlled gas units

Flow medium:

Butane, propane

Marking:

On orange cover "Continental TRIX® PROPAN / BUTAN DN 6,3 DIN EN 16436-1:2016 KLASSE-2 10-BAR DG4603CR0279 Made in Germany"

Standard / Approval:

DIN EN 16436-1:2016

Description:

- **Inner lining:** NBR, black, non-porous, smooth
- **Reinforcements:** Synthetic fibres
- **Cover:** NBR, orange, smooth, abrasion resistant, resistant to ozone, weather and UV
- **Working pressure up to:** 30 bar / 435 psi
- **Temperature range:** from -30 °C / -22 °F up to +70 °C / +158 °F
- **Further properties:**
 - Dimensionally stable
 - Highly flexible
 - Kink-resistant
 - Release agent- and fat free, free from product harmful to lacquer
 - Robust

Technical data:

INDEX									
nr	mm	mm	mm	m	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	6,3	3,5	13,3	40	10	30	-	25	135
-	6,3	5	16,3	40	30	90	-	20	233

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.