



TRIX ROTSTRAHL®

The professional water hose

Applications:

Agricultural sector, Fleets, General industry, Industry, Landscaping and gardening, Mining industry, Municipal enterprises, Over- and underground workings, Workshops

Flow medium:

Cooling water, Water

Marking:

6 red axially applied stripes on black cover "Continental TRIK ROTSTRAHL® DN 13 PN 20 BAR / 290 PSI Made in Germany"

Description:

- **Inner lining:** EPDM, black, non-porous, smooth
- **Reinforcements:** Synthetic fibres
- **Cover:** EPDM, black, smooth, from DN 28 upward fabric patterned, resistant to ozone, weather and UV
- **Working pressure up to:** 20 bar / 290 psi
- **Temperature range:** from -40 °C / -40 °F up to +100 °C / +212 °F
- **Further properties:**
 - Highly flexible
 - Low resistance to flow
 - Robust
 - Up to DN 25 release agent- and fat free, free from product harmful to lacquer

Technical data:

INDEX							
nr	mm	mm	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	13	19,6	20	60	-	50	245
-	13	19,6	20	60	-	50	245
-	13	19,6	20	60	-	50	245
-	16	23	20	60	-	60	330
-	19	27	20	60	-	65	435
-	19	27	20	60	-	65	435
-	19	27	20	60	-	65	435
-	22	31	20	60	-	70	520
-	25	34	20	60	-	110	580
-	25	34	20	60	-	110	580
-	28	38	15	45	-	120	715
-	30	41	15	45	-	140	835
-	32	43	15	45	-	170	890
-	35	46	15	45	-	180	940
-	38	50	15	45	-	200	1100
-	40	52	15	45	-	240	1150
-	42	54	10	30	-	250	1250
-	50	64	10	30	-	300	1565

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.