



UNITRIX® 60

The Allrounder

Applications:

Agricultural sector, Chemical and petrochemical industry, Construction industry, Forestry, Machinery and plant engineering, Mineral oil industry, Quarry, Railway industry, Shipping industry, Workshops

Flow medium:

Benzine, Butane, Cold water, Fuel oil, Gasoil, Hot water, Kerosene, Lubricating oil, Mineral oil, Naphtha, Oily air, Pesticides, Propane, Salt solutions

Marking:

6 tobacco brown coloured axial markings on black cover "Continental UNITRIX® 60 DN 13 PN 20 BAR / 290 PSI R < 106 Ω Made in Germany"

Description:

- **Inner lining:** NBR, black, non-porous, smooth
- **Reinforcements:** Synthetic fibres
- **Cover:** NBR, black, smooth, chemical-resistant, resistant to oil and fats, resistant to ozone, weather and UV
- **Working pressure up to:** 20 bar / 290 psi
- **Temperature range:** from -25 °C / -13 °F up to +85 °C / +185 °F
- **Further properties:**
 - Highly flexible
 - Length independently electrically conductive, R < 106 Ω
 - Release agent- and fat free, free from product harmful to lacquer
 - Robust

Technical data:

INDEX						aprx. mm	aprx. g/m
nr	mm	mm	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	6	13	20	60	-	25	160
-	8	15,5	20	60	-	35	210
-	10	17,5	20	60	-	40	250
-	13	21	20	60	-	55	320
-	16	25	20	60	-	65	430
-	19	29	20	60	-	85	550
-	25	36	20	60	-	115	760

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.