



GOLD SNAKE®

The high-grade water and cleaning hose

Applications:

Construction industry, General industry, Landscaping and gardening, Machinery and plant engineering, Municipal enterprises, Open land

Flow medium:

Cooling water, Water

Marking:

yellow wavy line on black cover, axially applied "Continental DN 13 Charge"

Description:

- **Inner lining:** EPDM, black, non-porous, smooth
- **Reinforcements:** Synthetic fibres
- **Cover:** CR, black, fabric patterned, abrasion resistant, chemical-resistant, resistant to oil and fats, resistant to ozone, weather and UV
- **Working pressure up to:** 30 bar / 435 psi
- **Temperature range:** from -30 °C / -22 °F up to +100 °C / +212 °F
- **Dampable up to:** +130 °C / +266 °F (max. 30 minutes)
- **Further properties:**
 - 5 years warranty
 - Can be overrun
 - Kink-resistant
 - Long-lasting
 - Shockproofs

Technical data:

INDEX							
nr	mm	mm	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	10	17,2	30	90	-	45	160
-	13	20,8	30	90	-	50	225
-	16	23,2	25	75	-	70	260
-	19	27,8	25	75	-	80	385
-	22	31	20	60	-	100	430
-	25	34	20	60	-	160	490
-	32	43	12	36	-	175	760
-	38	51	12	36	-	250	1050
-	45	60	10	30	-	290	1480
-	50	65	10	30	-	300	1580
-	75	91	10	30	-	700	2377

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability / Warranty only valid for proven cases of faulty materials and manufacturing, provided that couplings have been fitted by experts, that the recommended working conditions have been respected and that the hose has been used in accordance with its intended use.