



PARKING®

Applications:

Compressed air and compressor manufacturers, Largescale garages, Over- and underground workings, Petrol stations, Quarry, Shipyards, Steel and iron industry

Flow medium:

Compressed air, Pressurized air

Label:

6 blue stripes on black cover

Standard / Approval:

NFT 47252 B

Description:

- **Inner lining:** SBR, black, non-porous, smooth
- **Reinforcements:** Synthetic fibres
- **Cover:** SBR-EPDM, black, smooth, abrasion resistant, resistant to ozone, weather and UV
- **Working pressure up to:** 20 bar / 290 psi
- **Temperature range:** from -20 °C / -4 °F up to +65 °C / +149 °F
- **Further properties:**
 - Release agent- and fat free, free from product harmful to lacquer
 - Suitable for hot water for a short time up to +80°C / +176°F

Technical data:

INDEX						
nr	mm	mm	bar ¹	bar ¹	aprx. mm	aprx. g / m
-	6	13	20	60	-	170
-	6	13	20	60	-	170
-	8	15	20	60	-	200
-	8	15	20	60	-	200
-	10	17	20	60	-	250
-	10	17	20	60	-	250
-	13	21,6	20	60	-	350
-	13	21,6	20	60	-	350
-	19	30	20	60	-	580
-	19	30	20	60	-	580

* Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.