



THERMIDOR®

The versatile water hose

Applications:

Agricultural sector, Construction industry, Fleets, General industry, Industry, Landscaping and gardening, Mobile or stationary hose lines, Municipal enterprises

Flow medium:

Cooling water, Water

Marking:

3 yellow stripes, axially applied, on black cover "Continental THERMIDOR® DN 13 PN 15 BAR / 218 PSI Made in Germany"

Description:

- **Inner lining:** EPDM, black, non-porous, smooth
- **Reinforcements:** Synthetic fibres
- **Cover:** EPDM, black, smooth, resistant to ozone, weather and UV
- **Working pressure up to:** 15 bar / 218 psi
- **Temperature range:** from -40 °C / -40 °F up to +100 °C / +212 °F up to +120 °C / +248 °F short-time
- **Further properties:**
 - Flexible
 - Robust
 - Up to DN 25 release agent- and fat free, free from product harmful to lacquer

Technical data:

INDEX							
nr	mm	mm	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	13	19,6	15	45	-	105	215
-	13	19,6	15	45	-	105	215
-	15	21,6	15	45	-	120	280
-	15	21,6	15	45	-	120	280
-	19	26,6	15	45	-	150	390
-	19	26,6	15	45	-	150	390
-	25	33,6	15	45	-	200	550
-	25	33,6	15	45	-	200	550
-	30	39,6	10	30	-	240	720
-	30	39,6	10	30	-	240	720

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.