



TRIX® SUPER

The high-grade water hose

Applications:

Agriculture, Construction industry, Foundries, Machinery and plant engineering, Municipal enterprises, Oil and chemicals processing industry, Steel and iron industry

Flow medium:

Cooling water, Water

Marking:

2 yellow markings on black cover opposite each other " Continental TRIX® SUPER DN 13 PN 30 BAR / 435 PSI R < 106 Ω Made in Germany"

Description:

- **Inner lining:** EPDM, black, non-porous, smooth
- **Reinforcements:** Synthetic fibres
- **Cover:** EPDM, black, smooth, abrasion resistant, resistant to ozone, weather and UV
- **Working pressure up to:** 30 bar / 435 psi
- **Temperature range:** from -40 °C / -40 °F up to +120 °C / +248 °F
- **Further properties:**
 - Highly flexible
 - Length independently electrically conductive, $R < 106 \Omega$
 - Low resistance to flow
 - Release agent- and fat free, free from product harmful to lacquer
 - Robust

Technical data:

INDEX							
nr	mm	mm	bar ¹	bar ¹	bar ¹	aprx. mm	aprx. g/m
-	10	17	30	90	-	35	225
-	13	21	30	90	-	50	315
-	16	24	30	90	-	60	310
-	19	28	30	90	-	65	480
-	25	35	30	90	-	110	650

1 - Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability.