

Obejmy skorupowe z bolcem zgodnie EN 14420-3

Safety clamp with Pin EN 14420-3

index	materiał	wymiar	ciśnienie robocze	wąż	rozmiar
indeks	material	DN	WP	hose	size
DC25X6ALSF	Aluminum	25	25 bar	25*6	34-36
DC32X6ALSF	Aluminum	32	25 bar	32*6	40-43
DC38X6,5ALSF	Aluminum	38	25 bar	38*6,5	50 – 53
DC50X8ALSF	Aluminum	50	25 bar	50x8	63-67
DC65X7ALSF	Aluminum	65	25 bar	65x7	78-82
DC75X8ALSF	Aluminum	75	25 bar	75*8	89-93
DC100X8ALSF	Aluminum	100	25 bar	100*8	114-118



Obejmy skorupowe skręcane zgodnie EN 14420-3 – Śruby ze stali nierdzewnej

Safety clamp EN 14420-3 – Screws in Stainless Steel

index	materiał	wymiar	ciśnienie robocze	wąż	rozmiar	wkręt
indeks	material	DN	WP	hose	size	screw
DC13X5SS	SS AISI 316	13	25 bar	13*5	22-24	M6x20
DC19X6SS	SS AISI 316	19	25 bar	19*6	30-33	M6x20
DC25X6SS	SS AISI 316	25	25 bar	25*6	36-39	M6x20
DC32X6SS	SS AISI 316	32	25 bar	32*6	43-46	M6x20
DC38X6,5SS	SS AISI 316	38	25 bar	38*6,5	50-53	M6x20
DC38X8SS*	SS AISI 316	38	25 bar	38*8	53-56	M6x20
DC50X6SS*	SS AISI 316	50	25 bar	50*6	61-63	M8x25
DC50X8SS	SS AISI 316	50	25 bar	50*8	63-67	M8x25
DC50X10SS*	SS AISI 316	50	25 bar	50*10	69-71	M8x25
DC63X8SS	SS AISI 316	63	25 bar	63*8	78-82	M8x25
DC75X8SS	SS AISI 316	75	25 bar	75*8	89-93	M8x25
DC80X8SS	SS AISI 316	80	25 bar	80*8	94-97	M8x25
DC100X8SS	SS AISI 316	100	25 bar	100*8	114-119	M10x40
DC100X10SS	SS AISI 316	100	25 bar	100*10	118-122	M10x40



* Sonderabmessungen Special DN