

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ A – MIL A-A-59326A

– Wtyk z gwintem wewnętrznym BSPP

Male adapter type A – MIL A-A-59326A
with female BSPP thread

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
A050SS	SS AISI 316 / 1.4408	10 bar	DN15	1/2"
A075SS	SS AISI 316 / 1.4408	17 bar	DN20	3/4"
A100SS	SS AISI 316 / 1.4408	17 bar	DN25	1"
A125SS	SS AISI 316 / 1.4408	17 bar	DN32	1"1/4
A150SS	SS AISI 316 / 1.4408	17 bar	DN40	1"1/2
A200SS	SS AISI 316 / 1.4408	17 bar	DN50	2"
A250SS	SS AISI 316 / 1.4408	10 bar	DN65	2"1/2
A300SS	SS AISI 316 / 1.4408	8,5 bar	DN75	3"
A400SS	SS AISI 316 / 1.4408	6,5 bar	DN100	4"
A500SS	SS AISI 316 / 1.4408	5 bar	DN125	5"
A600SS	SS AISI 316 / 1.4408	5 bar	DN150	6"



Camlock Typ B – MIL A-A-59326A

– Gniazdo z gwintem zewnętrznym BSPT – Uszczelka NBR

Female coupler type B – MIL A-A-59326A
with male BSPT thread – NBR Gasket

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
B050SS2	SS AISI 316 / 1.4408	10 bar	DN15	1/2"
B075SS	SS AISI 316 / 1.4408	17 bar	DN20	3/4"
B100SS	SS AISI 316 / 1.4408	17 bar	DN25	1"
B125SS	SS AISI 316 / 1.4408	17 bar	DN32	1"1/4
B150SS	SS AISI 316 / 1.4408	17 bar	DN40	1"1/2
B200SS	SS AISI 316 / 1.4408	17 bar	DN50	2"
B250SS	SS AISI 316 / 1.4408	10 bar	DN65	2"1/2
B300SS	SS AISI 316 / 1.4408	8,5 bar	DN75	3"
B400SS	SS AISI 316 / 1.4408	6,5 bar	DN100	4"
B500SS	SS AISI 316 / 1.4408	5 bar	DN125	5"
B600SS	SS AISI 316 / 1.4408	5 bar	DN150	6"

