

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ C – MIL A-A-59326A

– Gniazdo z karbowanym ogonem – Uszczelka NBR

Female coupler type C – MIL A-A-59326A with grooved hose-shank

– NBR Gasket

index	materiał	ciśnienie robocze	wymiar	ogon
indeks	material	WP	dimension	shank
C050SS2	SS AISI 316 / 1.4408	10 bar	DN15	13 mm
C075SS	SS AISI 316 / 1.4408	17 bar	DN20	21 mm
C100SS	SS AISI 316 / 1.4408	17 bar	DN25	27 mm
C125SS	SS AISI 316 / 1.4408	17 bar	DN32	34 mm
C150SS	SS AISI 316 / 1.4408	17 bar	DN40	40 mm
C200SS	SS AISI 316 / 1.4408	17 bar	DN50	51 mm
C200x150SS	SS AISI 316 / 1.4408	17 bar	DN50	40 mm
C250SS	SS AISI 316 / 1.4408	10 bar	DN65	64 mm
C300SS	SS AISI 316 / 1.4408	8,5 bar	DN75	76 mm
C400SS	SS AISI 316 / 1.4408	6,5 bar	DN100	103 mm
C500SS	SS AISI 316 / 1.4408	5 bar	DN125	128 mm
C600SS	SS AISI 316 / 1.4408	5 bar	DN150	152 mm



Camlock Typ D – MIL A-A-59326A

– Gniazdo z gwintem wewnętrznym BSPP – Uszczelka NBR

Female coupler type D – MIL A-A-59326A

with female BSPP thread – NBR Gasket

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
D050SS2	SS AISI 316 / 1.4408	10 bar	DN15	1/2"
D075SS	SS AISI 316 / 1.4408	17 bar	DN20	3/4"
D100SS	SS AISI 316 / 1.4408	17 bar	DN25	1"
D125SS	SS AISI 316 / 1.4408	17 bar	DN32	1 1/4"
D150SS	SS AISI 316 / 1.4408	17 bar	DN40	1 1/2"
D200SS	SS AISI 316 / 1.4408	17 bar	DN50	2"
D250SS	SS AISI 316 / 1.4408	10 bar	DN65	2 1/2"
D300SS	SS AISI 316 / 1.4408	8,5 bar	DN75	3"
D400SS	SS AISI 316 / 1.4408	6,5 bar	DN100	4"
D500SS	SS AISI 316 / 1.4408	5 bar	DN125	5"
D600SS	SS AISI 316 / 1.4408	5 bar	DN150	6"

