

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ A – MIL A-A-59326A – Wtyk z gwintem wewnętrznym BSPP

Male adapter type A – MIL A-A-59326A with female BSPP thread

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
A050BR	Brass	10 bar	DN15	1/2"
A075BR	Brass	17 bar	DN20	3/4"
A100BR	Brass	17 bar	DN25	1"
A125BR	Brass	17 bar	DN32	1"1/4
A150BR	Brass	17 bar	DN40	1"1/2
A200BR	Brass	17 bar	DN50	2"
A250BR	Brass	10 bar	DN65	2"1/2
A300BR	Brass	8,5 bar	DN75	3"
A400BR	Brass	6,5 bar	DN100	4"
A500BR	Brass	5 bar	DN125	5"
A600BR	Brass	5 bar	DN150	6"



Camlock Typ B – MIL A-A-59326A – Gniazdo z gwintem zewnętrznym BSPT – Uszczelka NBR

Female coupler type B – MIL A-A-59326A with male BSPT thread – NBR Gasket

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
B050BR	Brass	10 bar	DN15	1/2"
B075BR	Brass	17 bar	DN20	3/4"
B100BR	Brass	17 bar	DN25	1"
B125BR	Brass	17 bar	DN32	1"1/4
B150BR	Brass	17 bar	DN40	1"1/2
B200BR	Brass	17 bar	DN50	2"
B250BR	Brass	10 bar	DN65	2"1/2
B300BR	Brass	8,5 bar	DN75	3"
B400BR	Brass	6,5 bar	DN100	4"
B500BR	Brass	5 bar	DN125	5"
B600BR	Brass	5 bar	DN150	6"

