

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ C – MIL A-A-59326A – Gniazdo z karbowanym ogonem pod opaski – Uszczelka NBR

Female coupler type C – MIL A-A-59326A with grooved hose-shank – NBR Gasket

index	materiał	ciśnienie robocze	wymiar	ogon
indeks	material	WP	dimension	shank
C050BR	Brass	10 bar	DN15	13 mm
C075BR	Brass	17 bar	DN20	21 mm
C100BR	Brass	17 bar	DN25	27 mm
C125BR	Brass	17 bar	DN32	34 mm
C150BR	Brass	17 bar	DN40	40 mm
C200BR	Brass	17 bar	DN50	51 mm
C250BR	Brass	10 bar	DN65	64 mm
C300BR	Brass	8,5 bar	DN75	76 mm
C400BR	Brass	6,5 bar	DN100	103 mm
C500BR	Brass	5 bar	DN125	128 mm
C600BR	Brass	5 bar	DN150	152 mm



Camlock Typ D – MIL A-A-59326A – Gniazdo z gwintem wewnętrznym BSPP – Uszczelka NBR

Female coupler type D – MIL A-A-59326A with female BSPP thread – NBR Gasket

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
D050BR	Brass	10 bar	DN15	1/2"
D075BR	Brass	17 bar	DN20	3/4"
D100BR	Brass	17 bar	DN25	1"
D125BR	Brass	17 bar	DN32	1 1/4"
D150BR	Brass	17 bar	DN40	1 1/2"
D200BR	Brass	17 bar	DN50	2"
D250BR	Brass	10 bar	DN65	2 1/2"
D300BR	Brass	8,5 bar	DN75	3"
D400BR	Brass	6,5 bar	DN100	4"
D500BR	Brass	5 bar	DN125	5"
D600BR	Brass	5 bar	DN150	6"

