

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ E – MIL A-A-59326A – Wtyk z karbowanym ogonem pod opaski

Male adapter type E – MIL A-A-59326A with grooved hose-shank

index	materiał	ciśnienie robocze	wymiar	ogon
indeks	material	WP	dimension	shank
E050BR	Brass	10 bar	DN15	13 mm
E075BR	Brass	17 bar	DN20	21 mm
E100BR	Brass	17 bar	DN25	27 mm
E125BR	Brass	17 bar	DN32	34 mm
E150BR	Brass	17 bar	DN40	40 mm
E200BR	Brass	17 bar	DN50	51 mm
E250BR	Brass	10 bar	DN65	64 mm
E300BR	Brass	8,5 bar	DN75	76 mm
E400BR	Brass	6,5 bar	DN100	103 mm
E500BR	Brass	5 bar	DN125	128 mm
E600BR	Brass	5 bar	DN150	152 mm



Camlock Typ F – MIL A-A-59326A – Wtyk z gwintem zewnętrznym BSPT

Male adapter type F – MIL A-A-59326A with male BSPT thread

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
F050BR	Brass	10 bar	DN15	1/2"
F075BR	Brass	17 bar	DN20	3/4"
F100BR	Brass	17 bar	DN25	1"
F125BR	Brass	17 bar	DN32	1 1/4"
F150BR	Brass	17 bar	DN40	1 1/2"
F200BR	Brass	17 bar	DN50	2"
F250BR	Brass	10 bar	DN65	2 1/2"
F300BR	Brass	8,5 bar	DN75	3"
F400BR	Brass	6,5 bar	DN100	4"
F500BR	Brass	5 bar	DN125	5"
F600BR	Brass	5 bar	DN150	6"

