

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ A – MIL A-A-59326A – Wtyk z gwintem wewnętrznym BSPP

Male adapter type A – MIL A-A-59326A with female BSPP thread

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
A050AL	Aluminum	10 bar	DN15	1/2"
A075AL	Aluminum	17 bar	DN20	3/4"
A100AL	Aluminum	17 bar	DN25	1"
A125AL	Aluminum	17 bar	DN32	1 1/4"
A150AL	Aluminum	17 bar	DN40	1 1/2"
A200AL	Aluminum	17 bar	DN50	2"
A250AL	Aluminum	10 bar	DN65	2 1/2"
A300AL	Aluminum	8,5 bar	DN75	3"
A400AL	Aluminum	6,5 bar	DN100	4"
A500AL	Aluminum	5 bar	DN125	5"
A600AL	Aluminum	5 bar	DN150	6"
A800AL	Aluminum	4 bar	DN200	8"



Camlock Typ B – MIL A-A-59326A – Gniazdo z gwintem zewnętrznym BSPT – Uszczelka NBR

Female coupler type B – MIL A-A-59326A with male BSPT thread – NBR Gasket

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
B050AL	Aluminum	10 bar	DN15	1/2"
B075AL	Aluminum	17 bar	DN20	3/4"
B100AL	Aluminum	17 bar	DN25	1"
B125AL	Aluminum	17 bar	DN32	1 1/4"
B150AL	Aluminum	17 bar	DN40	1 1/2"
B200AL	Aluminum	17 bar	DN50	2"
B250AL	Aluminum	10 bar	DN65	2 1/2"
B300AL	Aluminum	8,5 bar	DN75	3"
B400AL	Aluminum	6,5 bar	DN100	4"
B500AL	Aluminum	5 bar	DN125	5"
B600AL	Aluminum	5 bar	DN150	6"
B800AL	Aluminum	4 bar	DN200	8"

