

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ E – MIL A-A-59326A – Wtyk z karbowanym ogonem pod opaski

Male adapter type E – MIL A-A-59326A with grooved hose-shank

index	materiał	ciśnienie robocze	wymiar	ogon
indeks	material	WP	dimension	shank
E050AL	Aluminum	10 bar	DN15	13 mm
E075AL	Aluminum	17 bar	DN20	21 mm
E100AL	Aluminum	17 bar	DN25	27 mm
E125AL	Aluminum	17 bar	DN32	34 mm
E150AL	Aluminum	17 bar	DN40	40 mm
E200AL	Aluminum	17 bar	DN50	51 mm
E250AL	Aluminum	10 bar	DN65	64 mm
E300AL	Aluminum	8,5 bar	DN75	76 mm
E400AL	Aluminum	6,5 bar	DN100	103 mm
E500AL	Aluminum	5 bar	DN125	128 mm
E600AL	Aluminum	5 bar	DN150	152 mm
E800AL	Aluminum	4 bar	DN200	200 mm



Camlock Typ F – MIL A-A-59326A – Wtyk z gwintem zewnętrznym BSPT

Male adapter type F – MIL A-A-59326A with male BSPT thread

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
F050AL	Aluminum	10 bar	DN15	1/2"
F075AL	Aluminum	17 bar	DN20	3/4"
F100AL	Aluminum	17 bar	DN25	1"
F125AL	Aluminum	17 bar	DN32	1 1/4"
F150AL	Aluminum	17 bar	DN40	1 1/2"
F200AL	Aluminum	17 bar	DN50	2"
F250AL	Aluminum	10 bar	DN65	2 1/2"
F300AL	Aluminum	8,5 bar	DN75	3"
F400AL	Aluminum	6,5 bar	DN100	4"
F500AL	Aluminum	5 bar	DN125	5"
F600AL	Aluminum	5 bar	DN150	6"
F800AL	Aluminum	4 bar	DN200	8"

