

## ZŁĄCZA CAMLOCK EN 14420-7/MIL

### Camlock Typ A – MIL A-A-59326A – Wtyk z gwintem wewnętrznym BSPP

#### Male adapter type A – MIL A-A-59326A with female BSPP thread

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
A050PP	Polypropylene	8,5 bar	DN20	1/2"
A075PP	Polypropylene	8,5 bar	DN20	3/4"
A100PP	Polypropylene	8,5 bar	DN25	1"
A125PP	Polypropylene	6,5 bar	DN32	1"1/4
A150x125PP	Polypropylene	6,5 bar	DN40	1"1/4
A150PP	Polypropylene	6,5 bar	DN40	1"1/2
A200PP	Polypropylene	6,5 bar	DN50	2"
A300PP	Polypropylene	5 bar	DN75	3"
A400PP	Polypropylene	5 bar	DN100	4"



### Camlock Typ B – MIL A-A-59326A – Gniazdo z gwintem zewnętrznym BSPT – Uszczelka EPDM

#### Female coupler type B – MIL A-A-59326A with male BSPT thread – EPDM Gasket

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
B050PP	Polypropylene	8,5 bar	DN20	1/2"
B075PP	Polypropylene	8,5 bar	DN20	3/4"
B100PP	Polypropylene	8,5 bar	DN25	1"
B125PP	Polypropylene	6,5 bar	DN32	1"1/4
B150x125PP	Polypropylene	6,5 bar	DN40	1"1/4
B150PP	Polypropylene	6,5 bar	DN40	1"1/2
B200PP	Polypropylene	6,5 bar	DN50	2"
B300PP	Polypropylene	5 bar	DN75	3"
B400PP	Polypropylene	5 bar	DN100	4"

