

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ C – MIL A-A-59326A – Gniazdo z karbowanym ogonem pod opaski – Uszczelka EPDM

Female coupler type C – MIL A-A-59326A with grooved hose-shank – EPDM Gasket

index	materiał	ciśnienie robocze	wymiar	ogon
indeks	material	WP	dimension	shank
C050PP	Polypropylene	8,5 bar	DN20	13 mm
C075PP	Polypropylene	8,5 bar	DN20	21 mm
C100PP	Polypropylene	8,5 bar	DN25	27 mm
C125PP	Polypropylene	6,5 bar	DN32	34 mm
C150x125PP	Polypropylene	6,5 bar	DN40	34 mm
C150PP	Polypropylene	6,5 bar	DN40	40 mm
C200x100PP	Polypropylene	6,5 bar	DN50	27 mm
C200x150PP	Polypropylene	6,5 bar	DN50	40 mm
C200PP	Polypropylene	6,5 bar	DN50	51 mm
C300PP	Polypropylene	5 bar	DN75	76 mm
C400PP	Polypropylene	5 bar	DN100	103 mm



Camlock Typ D – MIL A-A-59326A – Gniazdo z gwintem wewnętrznym BSPP – Uszczelka EPDM

Female coupler type D – MIL A-A-59326A with female BSPP thread – EPDM Gasket

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
D050PP	Polypropylene	8,5 bar	DN20	1/2"
D075PP	Polypropylene	8,5 bar	DN20	3/4"
D100PP	Polypropylene	8,5 bar	DN25	1"
D125PP	Polypropylene	6,5 bar	DN32	1 1/4"
D150x125PP	Polypropylene	6,5 bar	DN40	1 1/4"
D150PP	Polypropylene	6,5 bar	DN40	1 1/2"
D200PP	Polypropylene	6,5 bar	DN50	2"
D300PP	Polypropylene	5 bar	DN75	3"
D400PP	Polypropylene	5 bar	DN100	4"

