

ZŁĄCZA CAMLOCK EN 14420-7/MIL

Camlock Typ E – MIL A-A-59326A – Wtyk z karbowanym ogonem pod opaski

Male adapter type E – MIL A-A-59326A with grooved hose-shank

index	materiał	ciśnienie robocze	wymiar	ogon
indeks	material	WP	dimension	shank
E050PP	Polypropylene	8,5 bar	DN20	13 mm
E075PP	Polypropylene	8,5 bar	DN20	21 mm
E100PP	Polypropylene	8,5 bar	DN25	27 mm
E125PP	Polypropylene	6,5 bar	DN32	34 mm
E150x125PP	Polypropylene	6,5 bar	DN40	34 mm
E150PP	Polypropylene	6,5 bar	DN40	40 mm
E200PP	Polypropylene	6,5 bar	DN50	51 mm
E300PP	Polypropylene	5 bar	DN75	76 mm
E400PP	Polypropylene	5 bar	DN100	103 mm



Camlock Typ F – MIL A-A-59326A – Wtyk z gwintem zewnętrznym BSPT

Male adapter type F – MIL A-A-59326A with male BSPT thread

index	materiał	ciśnienie robocze	wymiar	gwint
indeks	material	WP	dimension	thread
F050PP	Polypropylene	8,5 bar	DN20	1/2"
F075PP	Polypropylene	8,5 bar	DN20	3/4"
F100PP	Polypropylene	8,5 bar	DN25	1"
F125PP	Polypropylene	6,5 bar	DN32	1 1/4"
F150x125PP	Polypropylene	6,5 bar	DN40	1 1/4"
F150PP	Polypropylene	6,5 bar	DN40	1 1/2"
F200PP	Polypropylene	6,5 bar	DN50	2"
F300PP	Polypropylene	5 bar	DN75	3"
F400PP	Polypropylene	5 bar	DN100	4"

