

## ZŁĄCZA CAMLOCK EN 14420-7/MIL

### Akcesoria – łańcuszki i piny

#### Accessoiresug – Chain

index	materiał
indeks	material
36310	Brass
36310-SS	Stainless Steel
SS12CH	Stainless Steel
CGP	Steel



### Uszczelki gwintu do Camlock EN 14420

#### Thread gasket for Couplings EN 14420 couplings

index	kolor	materiał	wymiar
indeks	colour	material	dimension
SFPU13	Black	PU	DN13
SFPU19	Black	PU	DN19
SFPU25	Black	PU	DN25
SFPU32	Black	PU	DN32
SFPU38	Black	PU	DN38
SFPU50	Black	PU	DN50
SFPU65	Black	PU	DN64
SFPU80	Black	PU	DN75
SFPU100	Black	PU	DN100

SFPU13B	Blue	PU	DN13
SFPU19B	Blue	PU	DN19
SFPU25B	Blue	PU	DN25
SFPU32B	Blue	PU	DN32
SFPU38B	Blue	PU	DN38
SFPU50B	Blue	PU	DN50
SFPU65B	Blue	PU	DN64
SFPU80B	Blue	PU	DN75
SFPU100B	Blue	PU	DN100



**Uszczelki gwintu do Camlock EN 14420**

**Thread gasket for Couplings EN 14420 couplings**

index	kolor	materiał	wymiar
indeks	colour	material	dimension
SFPU13T	Transparent	PU	DN13
SFPU19T	Transparent	PU	DN19
SFPU25T	Transparent	PU	DN25
SFPU32T	Transparent	PU	DN32
SFPU38T	Transparent	PU	DN38
SFPU50T	Transparent	PU	DN50
SFPU65T	Transparent	PU	DN64
SFPU80T	Transparent	PU	DN75
SFPU100T	Transparent	PU	DN100



0.5TWTFG	White	PTFE – GF reinforced	DN13
0.75TWTFG	White	PTFE – GF reinforced	DN19
1TWTFG	White	PTFE – GF reinforced	DN25
1.25TWTFG	White	PTFE – GF reinforced	DN32
1.5TWTFG	White	PTFE – GF reinforced	DN38
2TWTFG	White	PTFE – GF reinforced	DN50
2.5TWTFG	White	PTFE – GF reinforced	DN64
3TWTFG	White	PTFE – GF reinforced	DN75
4TWTFG	White	PTFE – GF reinforced	DN100



**Uszczelki gniazda Camlock**

**Gasket for Camlock Female Coupling**

index	kolor	materiał	wymiar
indeks	colour	material	dimension
050B	black – blue Marking	NBR	DN15
075B	black – blue Marking	NBR	DN20
100B	black – blue Marking	NBR	DN25
125B	black – blue Marking	NBR	DN32
150B	black – blue Marking	NBR	DN40
200B	black – blue Marking	NBR	DN50
250B	black – blue Marking	NBR	DN65
300B	black – blue Marking	NBR	DN75
400B	black – blue Marking	NBR	DN100
500B	black – blue Marking	NBR	DN125
600B	black – blue Marking	NBR	DN150
800B	black – blue Marking	NBR	DN200

050E	black – white Marking	EPDM	DN15
075E	black – white Marking	EPDM	DN20
100E	black – white Marking	EPDM	DN25
125E	black – white Marking	EPDM	DN32
150E	black – white Marking	EPDM	DN40
200E	black – white Marking	EPDM	DN50
250E	black – white Marking	EPDM	DN65
300E	black – white Marking	EPDM	DN75
400E	black – white Marking	EPDM	DN100
500E	black – white Marking	EPDM	DN125
600E	black – white Marking	EPDM	DN150

050V	black yellow Marking	FKM (Viton®)	DN15
075V	black yellow Marking	FKM (Viton®)	DN20
100V	black yellow Marking	FKM (Viton®)	DN25
125V	black yellow Marking	FKM (Viton®)	DN32
150V	black yellow Marking	FKM (Viton®)	DN40
200V	black yellow Marking	FKM (Viton®)	DN50
250V	black yellow Marking	FKM (Viton®)	DN65
300V	black yellow Marking	FKM (Viton®)	DN75
400V	black yellow Marking	FKM (Viton®)	DN100
500V	black yellow Marking	FKM (Viton®)	DN125
600V	black yellow Marking	FKM (Viton®)	DN150

050H	green CSM	(Hypalon®)	DN15
075H	green CSM	(Hypalon®)	DN20
100H	green CSM	(Hypalon®)	DN25
125H	green CSM	(Hypalon®)	DN32
150H	green CSM	(Hypalon®)	DN40
200H	green CSM	(Hypalon®)	DN50
250H	green CSM	(Hypalon®)	DN65
300H	green CSM	(Hypalon®)	DN75
400H	green CSM	(Hypalon®)	DN100



**Uszczelki Camlock**

**Gasket for Camlock**

index	kolor	materiał	wymiar
indeks	colour	material	dimension
050TB	white – open laterally	NBR/PTFE	DN15
075TB	white – open laterally	NBR/PTFE	DN20
100TB	white – open laterally	NBR/PTFE	DN25
125TB	white – open laterally	NBR/PTFE	DN32
150TB	white – open laterally	NBR/PTFE	DN40
200TB	white – open laterally	NBR/PTFE	DN50
250TB	white – open laterally	NBR/PTFE	DN65
300TB	white – open laterally	NBR/PTFE	DN75
400TB	white – open laterally	NBR/PTFE	DN100

050TV	white – open laterally	FKM(Viton®)/PTFE	DN15
075TV	white – open laterally	FKM(Viton®)/PTFE	DN20
100TV	white – open laterally	FKM(Viton®)/PTFE	DN25
125TV	white – open laterally	FKM(Viton®)/PTFE	DN32
150TV	white – open laterally	FKM(Viton®)/PTFE	DN40
200TV	white – open laterally	FKM(Viton®)/PTFE	DN50
250TV	white – open laterally	FKM(Viton®)/PTFE	DN65
300TV	white – open laterally	FKM(Viton®)/PTFE	DN75
400TV	white – open laterally	FKM(Viton®)/PTFE	DN100

050TE	white – open laterally	EPDM/PTFE	DN15
075TE	white – open laterally	EPDM/PTFE	DN20
100TE	white – open laterally	EPDM/PTFE	DN25
125TE	white – open laterally	EPDM/PTFE	DN32
150TE	white – open laterally	EPDM/PTFE	DN40
200TE	white – open laterally	EPDM/PTFE	DN50
250TE	white – open laterally	EPDM/PTFE	DN65
300TE	white – open laterally	EPDM/PTFE	DN75
400TE	white – open laterally	EPDM/PTFE	DN100

050FEP	red – sheathed FEP	(Silicone core)	DN15
075FEP	red – sheathed FEP	(Silicone core)	DN20
100FEP	red – sheathed FEP	(Silicone core)	DN25
125FEP	red – sheathed FEP	(Silicone core)	DN32
150FEP	red – sheathed FEP	(Silicone core)	DN40
200FEP	red – sheathed FEP	(Silicone core)	DN50
300FEP	red – sheathed FEP	(Silicone core)	DN75
400FEP	red – sheathed FEP	(Silicone core)	DN100



## ZŁĄCZA CAMLOCK EN 14420-7/MIL

### Uszczelki Camlock – FDA

#### Gasket for Cam and Groove – FDA Confim

index	kolor	materiał	wymiar
indeks	colour	material	dimension
050E-FDA	white	EPDM	DN15
075E-FDA	white	EPDM	DN20
100E-FDA	white	EPDM	DN25
125E-FDA	white	EPDM	DN32
150E-FDA	white	EPDM	DN40
200E-FDA	white	EPDM	DN50
250E-FDA	white	EPDM	DN65
300E-FDA	white	EPDM	DN75

100S-FDA	red	Silicone	DN25
125S-FDA	red	Silicone	DN32
150S-FDA	red	Silicone	DN40
200S-FDA	red	Silicone	DN50
250S-FDA	red	Silicone	DN65
300S-FDA	red	Silicone	DN75

